

Accessories

Power Supplies

Industrial Power Supply

DR-4524

45W, 24 VDC, 0 to 2A DIN-Rail Power Supply, Input: 85 to 264 VAC; 120 to 370 VDC



Input:
85 to 264 VAC; 120 to 370 VDC
Output:
45W, 24 VDC, 0 to 2A
AC inrush current:
30A at 115 VAC, 60A at 230 VAC
Overload Protection:
105% to 150%
Over Voltage Protection:
115 to 135% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10 to 50°C
Operating Humidity:
20 to 90% RH
Safety Standards:
UL508, TUV EN60950-1
EMC Standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11
ENV50204
Weight:
0.31 kg
Dimensions:
78(W) x 93(H) x 67(D)mm

DR-75-24

75W, 24 VDC, 0 to 3.2A DIN-Rail Power Supply, Input: 85 to 264 VAC; 120 to 370 VDC



Input:
85 to 264 VAC; 120 to 370 VDC
Output:
75W, 24 VDC, 0 to 3.2A
AC inrush current:
30A at 115 VAC, 60A at 230 VAC
Overload Protection:
105% to 150%
Over Voltage Protection:
121 to 142% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10 to 60°C
Operating Humidity:
20 to 90% RH
Safety Standards:
UL508, TUV EN60950-1 approved
EMC Standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11
ENV50204
Weight:
0.6 kg
Dimensions:
55.5(W) x 125.2(H) x 100(D)mm

DR-120-24

120W, 24 VDC, 0 to 5A DIN-Rail Power Supply, Input: 88 to 132 VAC/ 176 to 264 VAC



Input:
88 to 132 VAC/ 176 to 264 VAC
selectable by switch
Output:
120W, 24 VDC, 0-5A
AC inrush current:
30A at 115 VAC, 60A at 230 VAC
Overload Protection:
105% to 150%
Over Voltage Protection:
120 to 140% of rated output voltage
Type:
Constant Current Limiting
Reset:
Auto Recovery

Operating Temperature:
-10 to 60°C
Operating Humidity:
20 to 90% RH
Safety Standards:
UL508, UL60950-1, TUV EN60950-1
approved
EMC Standards:
EN55022 class B, EN61000-3-2,3,
EN61000-6-2, EN61000-4-
2,3,4,5,6,8,11,
ENV50204
Weight:
0.79 kg
Dimensions:
65.5(W) x 125.2(H) x 100(D)mm

Power Supplies

Industrial Power Supply

DR-75-48

75W 48VDC DIN-Rail Power Supply, 85-264VAC input



Input:

85~264VAC; 120~370VDC

Output:

75W, 48 VDC, 0 to 1.6A

AC inrush current:

30A at 115VAC, 60A at 230VAC

Overload Protection:

105% to 150%

Over Voltage Protection:

121%~142% of rated output

voltage Type:

Constant Current Limiting

Reset:

Auto Recovery

Operating Temperature:-10 to 60°C

Operating Humidity:

20 to 90% RH

Safety Standards:

UL508, TUV EN60950-1 approved

EMC Standards:

EN55022 class B, EN61000-3-2,3,

EN61000-6-2, EN61000-4-

2,3,4,5,6,8,11

ENV50204

Weight:

0.6 kg

Dimensions:

55.5(W) x 125.2(H) x 100(D)mm

U65S111-P2J:

80W 48VDC Power Supply



Input:

95~264VAC

Output:

80W, 48 VDC, 1.66A

AC inrush current:

40A at 230VAC

Overload Protection:

Hiccup mode, auto-recovery

Over Voltage Protection:

110%~140% of rated output voltage

Operating Temperature:0 to 40°C

Safety Standards:

UL1950, TUV EN60950 approved

EMC Standards:

EN55022 class B, EN61000-3-2,3,

EN61000-4-2,3,4,5,6,8,11

Dimensions:

168(W) x 79(H) x 45(D)mm

Power Supplies

Industrial Power Supply

DRP-240-24

240W, 24 VDC, 0 to 10A DIN-Rail Power Supply, Input: 85 to 264 VAC/ 120 to 370 VAC



Input:

85 to 264 VAC; 120 to 370 VDC

Output:

240W, 24 VDC, 0 to 10A

AC inrush current:

27A at 115 VAC, 45A at 230 VAC

Overload Protection:

105% to 150%

Over Voltage Protection:

30 to 36V

Type:

Constant Current Limiting

Reset:

Auto Recovery

Operating Temperature:

-10 to 55°C

Operating Humidity:

20 to 90% RH

Safety Standards:

UL508, UL60950-1, TUV EN60950-1

EMC Standards:

EN55022 class B, EN61000-3-2,3,

EN61000-6-2, EN61000-

4-2,3,4,5,6,8,11

ENV50204

Weight:

1.2 kg

Dimensions:

125.5(W) x 125.2(H) x 100(D)mm

DRP-480S-24

480W, 24 VDC, 0 to 20A DIN-Rail Power Supply, Input: 90 to 132 VAC/ 180 to 264 VAC



Input:

90 to 132 VAC; 180 to 264 VDC
selectable by switch

Output:

480W, 24 VDC, 0 to 20A

AC inrush current:

45A at 230 VAC

Overload Protection:

105% to 150%

Over Voltage Protection:

30 to 36V

Type:

Constant Current Limiting

Reset:

Auto Recovery

Operating Temperature:

-20 to 50°C

Operating Humidity:

20 to 90% RH

Safety Standards:

UL508, UL60950-1, TUV EN60950-1

EMC Standards:

EN61000-6-2,

EN61000-4-2,3,4,5,6,8,11,

ENV50204, EN61204-3

Weight:

2.6 kg

Dimensions:

227(W) x 125.2(H) x 100(D)mm